

# DURACELL®

## POWERPACK 600

Portable & Emergency  
Power



### Heavy Duty Portable Power for Work, Play, and Emergencies

The Duracell® Powerpack 600 provides heavy duty household power anywhere. It operates demanding applications such as power tools, powers DC products that you enjoy during outdoor recreation, and provides emergency power during an outage at home. The Powerpack 600 is quiet, dependable and an easy-to-use alternative to a generator, with added features such as jumper cables. The integrated AM/FM radio and digital alarm clock provide access to music, talk radio and news. Whether it's a job site or a camp site, the Duracell® Powerpack 600 is the ideal portable power solution.

#### Product Features:

- ▶ Runs 120-volt AC applications (three outlets)
- ▶ Runs 12-volt DC applications (one outlet)
- ▶ Built-in 600-watt inverter
- ▶ Integrated AM/FM radio and digital alarm clock
- ▶ Included jumper cables are designed for safe and efficient jump-starting
- ▶ Built-in light provides illumination in emergency situations at home and on the road
- ▶ Recharge at home or from a vehicle

#### Product Applications:

- ▶ Runs small power tools at a work site
- ▶ Operates camcorders, video games, stereos, 13" TV/VCR combos, handheld blenders, fans, computers, laptops, clock radios
- ▶ Charges cordless and cellular phones
- ▶ Jump-starts vehicles
- ▶ Built-in AM/FM radio provides access to news radio and emergency broadcasts



Portable power anywhere



Vehicle jump-starter

#### Retail Package



[www.duracellpower.com](http://www.duracellpower.com)

### Product Specifications

#### AC

AC output power (max. continuous)	480 W
AC output power (5 min)	600 W
AC output surge capacity (peak)	960 W
AC output voltage (nominal)	120 V
AC output frequency	60 Hz
AC output waveform	Modified sine wave
Inverter no-load current	< 0.20 amps (battery drain with no load on inverter)
Inverter low-battery alarm	11.0 V
Inverter low-battery shutdown	10.5 V

#### DC

Internal battery type	Sealed lead-acid, AGM
Internal battery capacity	28 Ah, 280 CCA
Internal battery voltage	12 Vdc (nominal)
DC power socket (circuit breaker)	12 A (automatic reset)

### General Specifications

Part number	852-2007
Unit dimensions (L x W x H)	19.25 x 8.25 x 11.25" (48.9 x 21 x 28.6 cm)
Unit weight	58.2 lb (26.4 kg)
Warranty	Six months
Operating temperature	32°F to 104°F (0°C to 40°C)
Storage temperature	32°F to 86°F (0°C to 30°C)

Jump-start cables	24" (610 mm), 4 AWG
Radio	AM 526 - 1606 kHz / FM 82 - 105 MHz
Flashlight	5 W (replaceable)

### Charging System

AC charger bulk charging current	1 A (maximum)
Peak charging voltage	14.2 V (nominal)
Charge restart voltage	12.9 V (nominal)
Float charge current	1 mA (nominal)
Charger input socket current	2.5 A (maximum)

### Charging Time

From AC outlet	Max. 35 hours*
From DC outlet	Max. 4 hours*


\*Maximum charging time occurs when battery is completely discharged

### Packaging Specifications

	Retail Package*	Master Carton	Pallet
Size (L x W x H)	15.5 x 11 x 13.5" (42 x 28 x 35 cm)	16.75 x 11.5 x 14.2" (42.5 x 29.2 x 36.2 cm)	40 x 48 x 75.25" (101.6 x 121.9 x 191.1 cm)
Count	1	1	40
Weight	32 lb (14.5 kg)	34 lb (15.4 kg)	N/A
Volume	N/A	5444 cu.in.	N/A
UPC number	715535890025		

\* Box

Specifications subject to change without notice



### Xantrex Technology Inc.

Headquarters	5916 195th Street NE
8999 Nelson Way	Arlington, Washington
Burnaby, British Columbia	USA 98223
Canada V5A 4B5	