

DURACELL®

INSTANT JUMPSTART SYSTEM

Emergency Power



Jump-start your vehicle without another vehicle

The Duracell® Instant Jumpstart System is ideal for emergency situations when you're on the road or at home. It's convenient and easy to use to jump-start your vehicle without needing another vehicle, and has a built-in incandescent light that provides illumination for any emergency. The Duracell® Instant Jumpstart System also provides backup DC power for cell phones, laptops, digital cameras and other small, portable devices.

Product Features:

- ▶ 400-amp starting capacity
- ▶ Built-in light for emergency situations
- ▶ One DC socket for operating 12-volt devices
- ▶ LED gauge for monitoring the battery state-of-charge
- ▶ Jump-start cable conveniently attached to the unit for neat, easy storage



Emergency jump-start for your vehicle

Retail Package



www.duracellpower.com

Product Specifications

DC

Internal battery type	Sealed lead-acid, AGM
Internal battery capacity	17 Ah, 170 CCA
Internal battery voltage	12 Vdc
DC power socket (circuit breaker)	15 A (user-replaceable fuse)

General Specifications

Part number	854-1707
Unit dimensions (L x W x H)	9.25 x 6 x 12.5" (23.5 x 15.2 x 31.8 cm)
Unit weight	14.5 lb (6.6 kg)
Warranty	Three months
Operating temperature	32°F to 104°F (0°C to 40°C)
Storage temperature	32°F to 86°F (0°C to 30°C)
Jump-start cables	39", 9 AWG
Ambient light	3 W

Charging System

AC charger bulk charging current	350 mA (maximum)
Peak charging voltage	14.5 V (nominal)
Charge restart voltage	12.9 V (nominal)
Charger input socket current	2 A (maximum)

Charging Time

From AC outlet	Max. 48 hours*
From DC outlet	Max. 4 hours*


*Maximum charging time occurs when battery is completely discharged

Packaging Specifications

	Retail Package*	Master Carton*	Pallet
Size (L x W x H)	10.5 x 7.875 x 13.5" (26.7 x 19.8 x 34.3 cm)	10.75 x 8.25 x 14" (27.3 x 21 x 35.6 cm)	40 x 48 x 74.5" (101.6 x 121.9 x 189.2 cm)
Count	1	1	80
Weight	17 lb (7.7 kg)	18 lb (8.2 kg)	N/A
Volume	N/A	1,242 cu.in.	N/A
UPC number	715535890070		

* Box

Specifications subject to change without notice



Xantrex Technology Inc.

Headquarters
8999 Nelson Way
Burnaby, British Columbia
Canada V5A 4B5

5916 195th Street NE
Arlington, Washington
USA 98223